



Description:

- 01 Pro Roofing[®] Felt is a polyester saturated asphalt membrane.
- 02 It has an imperishable and long lasting defense system.
- 03 It helps in fighting against dampness, leakage and seepage.

Salient Features:

- ✔ High Flexibility
- ✔ Does Not Crack
- ✔ Does not shrink or expand
- ✔ Heating or blowing not required
- ✔ Resistance against high temperatures

Material Handling & Safety:

- ✔ Can be used anywhere in a building
- ✔ No environmental hazard
- ✔ No toxic effect
- ✔ Always wear the proper clothing and protective equipment when handling hot bitumen.
- ✔ Always walk flat-footed on a roof.
- ✔ Always have a clear path and look out for pipes, anchors, jacks, openings and hazards.
- ✔ Never lift a filled bucket above hip height. Wood sheathing or deck should not be less than [12.7 mm (1/2 in) x 400 mm (16 in)].

TECHNICAL DATA:

ASTM D-312, D-146, D-5147

Net Mass of Saturated 13-15Kg

Felt 1 x 10 m Roll

Moisture < 4.0%

Ash Content 10.00%

Size 31' x 3'- 6'

Available 62' x 3'- 6'

**Pro Roofing[®] Flet is fully compliance with
BS 6229:2018 Roofing System**

Note: Pro Roofing Flet is available with different base material, Fiber based, Glass Fiber based, Asbestos based, Jute based, Aluminum Foil based. Upon request customize lenght can make.